

Muld-Purpose Reck Fem

Reversible Alfilow Quickly Leat Transfer Low Power Consumption Silent Operation Witteless Remote Controller
















Roof window



Silent operation Reversible airflow Timer setting

Regulated airflow



Reversible airflow control with 6 speed levels, 7 levels timer setting and easily operable panel.

Adjustable handle clips design for mounting at 380- 550 mm roof windows

Roof window can be closed or opened without dismounting the double fan

Quickly heat transfer and regulated circulation

Equipped TITAN exclusive 9-blades silent fans for quite operation

















Specification	TTC-SC21/V
Outline Dimension	Fan specification 320 x156 x34mm
Fan Dimension	140 x140 x25mm *2
Input Voltage	12V DC
Rated Current	<1.1A

Power Consumption <13.2W Rated Speed 600-2200 RPM Airflow Noise Level 7 - 32 dBA

76.4 - 280 CFM Static Pressure 0.05 - 1.0 InchH20 Bearing Type Z-AXIS Life Time 60,000

6 levels speed			
Level 1	600 RPM	MIN	
Level 2	1000 RPM	20%	
Level 3	1400 RPM	40%	
Level 4	1600 RPM	60%	
Level 5	1900 RPM	80%	
Level 6	2200 RPM	100%	

Wireless remote controller

Controller dimension: 87 x40 x6.7mm Battery type: CR2025 Battery voltage: 3V Control range: 3M